

PD, PD150, PD2000

Paraffin/Ashphaltene Solvent Remover

DESCRIPTION

Blentex provides three strengths of a proprietary blend of solvents and dispersants that is extremely effective in removing and dispersing wax deposits from storage tanks, pipelines, down-hole, and surface equipment in the removal of heavy hydrocarbons from formation surfaces.

APPLICATION

PD, PD150 and PD2000 is best applied in batch applications for paraffin removal from tubing and rods. Treatment rates vary depending on severity of paraffin depositions. Treatment frequencies range from weekly to monthly batch applications at volumes of 5 to 20 gallons per treatment. Pipeline batch or flooded applications are strictly done depending on severity of paraffin depositions and can be calculated using the following suggestion: 168 gallons (4 bbl.) of PD2000 specialty formulation pumped or sprayed neat followed by 1,680 gallons (40 bbl.) of clean water. Repeat process until desired cleanliness of pipeline. PD2000 should be pumped neat either continuous or batched typically at rates of 100 ppm – 500 ppm due to severity of paraffin depositions.

"Empty" containers may retain residue (liquid and/or vapor) and can be dangerous. Do not pressure, cut, weld, braze solder, drill, grind or expose such containers to heat, flame, sparks or other forms of ignition. "Empty" containers should be drained, properly bunged and returned to a container reconditioner. Avoid prolonged contact with skin and frequently change soiled clothing. In case of contact, wash thoroughly with soap and water for 15 minutes or until the irritation subsides. The formation of mists should be avoided. Do not take internally. If swallowed, do not induce vomiting. Call physician or Poison Control Center immediately. Keep out of reach of children.

FEATURES & BENEFITS

Blentex paraffin dispersants are very effective treatments dissolving and dispersing paraffin build up causing high pressures in crude pipelines. They are highly effective as a formation cleaner for stripping heavy hydrocarbons from formation surfaces. These paraffin dispersants are designed specifically for higher gravity crudes that contain a high wax content, but is also effective on lower gravity crudes. Our products provide a fast dispersion of waxes allowing the material to be quickly removed from down-hole services. PD, PD150 and PD2000 are very effective treatments for dissolving and dispersing paraffin build up (BSW Bottoms) in crude storage tanks.

PROPERTIES

Test	Typical Inspections
Appearance	Clear Liquid
Flash Point	65° F
Density lbs./gal	6.2
Sp. Gravity	.772

*The values shown here are typical and may vary within modest ranges.



Blentex Industries, LLC
4760 Preston Rd
Frisco, TX 75034
www.blentexindustries.com

BLENTEX